

[HOME](#)[ABOUT US](#)[PRODUCTS](#)[SUPPORT](#)[EVENTS & TRAINING](#)[SALES OFFICES](#)[CONTACT US](#)[HOME](#) > [PRODUCTS](#) > [ACCESSORIES](#) > [OTHER ACCESSORIES](#)

## Other Accessories


**Item**      **Description**
**39085**      Large Shipping Case

This shipping case is a hard plastic case used for shipping Associated Research testers.

Compatible Models:  
OMNIA, HypotULTRA III and HypotMAX


**39001**      Small Shipping Case

This shipping case is a hard plastic case used for shipping Associated Research testers.

Compatible Models:  
3605, 3665, 3670, 3705, 3765, 3770, 3130, 3140


**38321**      Half Rack Mount Kit 2U

The rack mount kit is used as a shelf to connect the HYAMP III model 3130 and any Hypot III model together. The rack mount kit enables both instruments to be mounted side by side in a 19" rack. It also provides the necessary flanges for easy mounting and handles for easy removal.

Compatible Models:  
3130, 3140, 3605, 3665, 3670, 3705, 3765, 3770


**38075**      Interlock Connector

For stand-alone operation of many of our instruments, it is necessary (if no PLC cable is connected to the remote input) to disable the remote interlock function by plugging the 38075 interlock connector into the remote input connector found on the rear panel.

Compatible Models:  
3130, 3140, 3160, 3605, 3665, 3670, 3705, 3765, 3770, 4500D, 7620, 7650, 8004, 8005, 8006, 905D, 7700, 7704, 7705, 7710, 7715, 7720, 8104, 8105, 8106, 620L


**38142**      Interlock Connector Pass Thru

Male / Female pass through interlock connector. For stand-alone operation of many of our instruments, it is necessary (if no PLC cable is connected to the remote input) to disable the remote interlock function.

Compatible Models:  
3130, 3140, 3160, 3605, 3665, 3670, 3705, 3765, 3770, 4500D


**38807**      Data Storage card kit

This kit provides an additional interface option for the OMNIA series of electrical safety testers. Included in the kit is a 256 MB Flash memory stick.

Compatible Models:  
8104, 8105, 8106 Firmware version 3.21 or higher  
7620, 7650 Firmware version 2.40 or higher, other versions may require upgrade.


**38803**      256 MB Flash Memory

This 256 MB flash memory stick is designed to be used the Data Storage kit.

Compatible Models:  
Compatible with Data Storage card (38807)


**38819**      Ethernet Communication Card

The Ethernet Communication Card provides an interface option that allows for instrument control through a PC with a network connection.

Compatible Models:  
8104, 8105, 8106 Firmware version 3.30 or higher, other versions may require upgrade.  
7620, 7650 Firmware version 2.40 or higher, other versions may require upgrade.



**260-01** Interface Kit - 3130 to Hypot III

This kit provides the necessary cables to interconnect any Hypot III model to the HYAMP III model 3130.

Compatible Models:  
3130, 3605, 3665, 3670, 3705, 3765, 3770



**260-02** Interface Kit - 3160 to Hypot III

This kit provides the necessary cables to interconnect any Hypot III model to the HYAMP III model 3160.

Compatible Models:  
3160, 3605, 3665, 3670, 3705, 3765, 3770



**260-03** Interface Kit - 3140 to Hypot III

This kit provides the necessary cables to interconnect any Hypot III model to the HYAMP III model 3140.

Compatible Models:  
3140, 3605, 3665, 3670, 3705, 3765, 3770



**MANUAL** Owner's Manual (hard copy)

The most recent version of our Owner's Manuals are available in hard copy format.

Compatible Models:  
All active models



**33189** Input Power cable for Associated Research testers.

Compatible Models:  
All active models



**35822** Foot Switch

The foot switch is ideal to be used in applications where an operator needs to start a test with "hands off" the instrument.

Compatible Models:  
All hipot testers



**HS-8-12** Cable Assembly HV

This item comes standard with SC6540 scanning matrix. It is a high voltage wire that will interconnect between either of our scanners and one of our fully-automated testers.

Compatible Models:  
HS-8A, HS-16, SC6540



**35445** 120K Ohm Resistor

This precision 1% resistor is ideal as a load to set current trip points to meet safety agency specifications. Ideal for meeting the 120 Kohm requirements as called out in UL and other agency specifications.

Compatible Models:  
All hipot testers



**39067** DUT Enclosure

This DUT Enclosure is designed with an safety interlock that will eliminate the potential for electrical shock when used correctly. The interlock will disable the high voltage if the enclosure door is open. The DUT Enclosure is designed to be used with all interlocked Associated Research Hipot testers.

Outside dimensions:  
24"w x 19"d x 11.5"h  
610 mm w x 483 mm d x 293 mm h

Inside dimensions:  
20"w x 16"d x 10"h  
508 mm w x 407 mm d x 254 mm h

Compatible Models:  
All Hipot Testers with Interlock