



Language: UNITED STATES-ENGLISH

Instruments for **ELECTRICAL SAFETY COMPLIANCE TESTING**Product Quick Select: [HOME](#)[ABOUT US](#)[PRODUCTS](#)[SUPPORT](#)[EVENTS & TRAINING](#)[SALES OFFICES](#)[CONTACT US](#)[HOME](#) > [PRODUCTS](#) > [ACCESSORIES](#) > [PROBES & TEST LEADS](#)

Probes and Test Leads

Probes

**Item****Description****38081**

HV Retractable Probe

A retractable high voltage probe for safe testing and application of high voltage. Pressing the red push button extends the probe tip. Upon release of the button the probe tip retracts back into the sleeve.

Compatible Models:

36XX, 37XX, 55XX, 75XXDT & 76XX (excluding 7510DT and 7512DT)

**38082**

Return Retractable Probe

A retractable return probe. Pressing the black push button extends the probe tip. Upon release of the button the probe tip retracts back into the sleeve.

Compatible Models:

36XX, 37XX, 55XXDT, 75XXDT & 76XX (excluding 7510DT and 7512DT)

**38814**

Safe-T Probe

High voltage test gun has a unique dual action test trigger that controls the retractable probe tip and activates the high voltage circuit of the instrument. The probe has a unique ergonomic shape for ease of use.

Compatible Models:

4500D, 36XX, 37XX, 76XX, 7700, 7704, 810X

**38815**

Safe-T Probe 20 Ft.

20 Ft. high voltage test gun has a unique dual action test trigger that controls the retractable probe tip and activates the high voltage circuit of the instrument. The probe has a unique ergonomic shape for ease of use.

Compatible Models:

4500D, 36XX, 37XX, 76XX, 7700, 7704, 810X

**38694**

20 KV Probe

This is a high voltage test probe for our 7715 and 7720. It allows for the application of hipot test voltage to specific points on the Device Under Test (DUT).

Compatible Models:

7715, 7720

**38084**

Ground Bond Probe 4W w/ Lemo & Switch

This is a fixed tip 4-wire Ground Bond probe with a lemo connector. It allows easy contact with grounding points of the device under test. The probe has two separate test buttons that allow it to be comfortably used in various positions. The test switch can be used to activate high current after making good contact with the test point. The probe comes with three different styles of probe tips making it flexible enough to test a wide range of products.

Compatible Models:

3130, 5030DT, 7504SA, 7564SA, 7704, 8004

**38085**

Ground Bond Probe 2W w/ Lug & Switch

This is a fixed tip 2-wire Ground Bond probe with a lug connector. It allows easy contact with grounding points of the device under test. The probe has two separate test buttons that allow it to be comfortably used in various positions. The test switch can be used to activate high current after making good contact with the test point. The probe comes with three different styles of probe tips making it flexible enough to test a wide range of products.

Compatible Models:
8005, 8006

38538 4 wire, 40 Amp Ground Bond Probe with Kelvin Lead



This is a fixed tip 4 wire probe used with our 40 Amp Ground Bond testers. It allows easy contact with grounding points of the device under test. The probe has two separate test buttons that allow it to be comfortably used in various positions. The test switch can be used to activate high current after making good contact with the test point. The probe comes with three different styles of probe tips making it flexible enough to test a wide range of products.

Compatible Models:
3140, 8104

38539 2 wire, 40 Amp Ground Bond Probe with Lug



This is a fixed tip 2 wire probe used with our 40 Amp Ground Bond testers. The probe has two separate test buttons that allow it to be comfortably used in various positions. The test switch can be used to activate high current after making good contact with the test point. The probe comes with three different styles of probe tips making it flexible enough to test a wide range of products.

Compatible Models:
8105, 8106

Test Leads

4040A-08 Standard 5 Foot Hipot Lead



This is our standard high voltage test lead for applying the hipot test voltage to the Device Under Test (DUT). The test lead is 5 foot in length and is terminated in an alligator clip that allows for easy application of the test voltage.

Compatible Models:
3605, 3665, 3670, 3705, 3765, 3770, 4500D, 5500DT, 5560DT, 7500DT, 7504SA, 7510DT, 7512DT, 7564SA, 7620, 7650, 7700, 7704, 8004, 8005, 8006, 8104, 8105, 8106

CBLHV-15 15 Foot Hipot Lead



This is a 15 foot high voltage test lead for applying hipot test voltage to the DUT. The test lead is terminated in an alligator clip that allows for easy application of the test voltage.

Compatible Models:
3605, 3665, 3670, 3705, 3765, 3770, 4500D, 5500DT, 5560DT, 7500DT, 7504SA, 7510DT, 7512DT, 7620, 7650, 7700, 7704, 8004, 8005, 8006, 8104, 8105, 8106

CBLHV-25 25 Foot Hipot Lead



This is a 25 foot high voltage test lead for applying hipot test voltage to the DUT. The test lead is terminated in an alligator clip that allows for easy application of the test voltage.

Compatible Models:
3605, 3665, 3670, 3705, 3765, 3770, 4500D, 5500DT, 5560DT, 7500DT, 7504SA, 7510DT, 7512DT, 7620, 7650, 7700, 7704, 8004, 8005, 8006, 8104, 8105, 8106

38712 12 KV 5 Foot Hipot Lead



This is our high voltage lead for the 7705 and the 7710. It allows for the application of hipot test voltage to the Device Under Test (DUT). The test lead is 5 foot in length and is terminated in an alligator clip.

Compatible Models:
7705, 7710

38784 12 KV 15 Foot Hipot Lead



This is our 15 Foot high voltage lead for the 7705 and the 7710. It allows for the application of hipot test voltage to the Device Under Test (DUT). The test lead is 15 foot in length and is terminated in an alligator clip.

Compatible Models:
7705, 7710

38686 20 KV 5 Foot Hipot Lead



This is our high voltage lead for our 7715 and 7720. It allows for the application of the hipot test voltage to the Device Under Test (DUT). The test lead is 5 foot in length and is terminated in an alligator clip.

Compatible Models:
7715, 7720

2100A-13 Standard 5 Foot Hipot Return Lead



This is our standard return lead. It allows hipot test voltage to return to the hipot tester. The test lead is 5 foot in length and is terminated in an alligator clip.

Compatible Models:
510L, 520L, 3605, 3665, 3670, 3705, 3765, 3770, 4500D, 5500DT, 5560DT, 7500DT, 7510DT, 7512DT, 7620, 7650, 7700, 7704, 8005, 8006, 8105, 8106

This is a 15 foot hipot return lead. It allows hipot test voltage to return to the hipot tester and is terminated in an alligator clip.

Compatible Models:
3605, 3665, 3670, 3705, 3765, 3770, 4500D, 5500DT, 5560DT, 7500DT, 7510DT, 7512DT, 7620, 7650, 7700, 7704, 8004



CBLSR-25 25 Foot Hipot Return Lead

This is a 25 foot hipot return lead. It allows hipot test voltage to return to the hipot tester and is terminated in an alligator clip.

Compatible Models:
3605, 3665, 3670, 3705, 3765, 3770, 4500D, 5500DT, 5560DT, 7500DT, 7510DT, 7512DT, 7620, 7650, 7700, 7704, 8004



CBLSR-05M 5 Foot Hipot Return Lead w/ Magnet

This is a 5 foot hipot return lead. It allows hipot test voltage to return to the hipot tester and is terminated in a magnetic clip that provides easy application to the DUT.

Compatible Models:
3605, 3665, 3670, 3705, 3765, 3770, 4500D, 5500DT, 5560DT, 7500DT, 7510DT, 7512DT, 7620, 7650, 7700



38736 20 KV 5 Foot Hipot Return

This is our return lead for our HypotMAX, high voltage models. It allows hipot test voltage to return to the hipot test. The test lead is 5 foot in length and is terminated in an alligator clip.

Compatible Models:
7705, 7710, 7715, 7720



38786 20 KV 15 Foot Hipot Return

This is our 15 foot return lead for our HypotMAX, high voltage models. It allows hipot test voltage to return to the hipot tester. The test lead is 15 foot in length and is terminated in an alligator clip.

Compatible Models:
7705, 7710, 7715, 7720



5002D-24 Standard 5 Foot Ground Bond Lead

This is our standard Ground Bond test lead for applying ground bond test current to the DUT. The test lead is 5 foot in length and is terminated in an alligator clip that allows for easy application of the test voltage.


Compatible Models:
3130, 5030DT, 7504SA, 8004, 8005, 8006



CBLHC-15 15 Foot Ground Bond Lead

This is a 15 foot Ground Bond return lead. It allows ground bond test current to return to the ground bond tester. The test lead is terminated in an alligator clip.

Compatible Models:
3130, 5030DT, 7504SA, 8004, 8005, 8006



38489 40 Amp Ground Bond HC Lead

This is our standard 40 Amp Ground Bond test lead for applying ground bond test current to the DUT. The test lead is 5 foot in length and is terminated in an alligator clip that allows for easy application of test current.


Compatible Models:
3140, 8104, 8105, 8106



38621 10 Ft 40 Amp Ground Bond HC Lead

This is our 40 Amp Ground Bond test lead for applying ground bond test current to the DUT. The test lead is 10 foot in length and is terminated in an alligator clip that allows for easy application of test current.

Compatible Models:
3140, 8104, 8105, 8106



38622 15 Ft 40 Amp Ground Bond HC Lead

This is our 40 Amp Ground Bond test lead for applying ground bond test current to the DUT. The test lead is 15 foot in length and is terminated in an alligator clip that allows for easy application of test current.

Compatible Models:
3140, 8104, 8105, 8106

This is our 40 Amp Ground Bond test lead for applying ground bond test current to the DUT. The test lead is 25 foot in length and is terminated in an alligator clip that allows for easy application of test current.

Compatible Models:
3140, 8104, 8105, 8106



38429 5 Foot 60 Amp Ground Bond Lead

This is a five foot high current Ground Bond test lead for applying ground bond test current to the DUT. This lead comes standard with the 3160 and features a 4-wire connection to the tester. It is terminated in an alligator clip.

Compatible Models:
3160



5002D-37 Standard 5 Foot Ground Bond Return Lead

This is our standard Ground Bond return lead. It allows ground bond test current to return to the ground bond tester. The test lead is 5 foot in length and is terminated in an alligator clip.

Compatible Models:
3130, 5030DT, 7504SA, 7704, 8004, 8005, 8006



CBLHR-15 15 Foot Ground Bond Return Lead

This is a 15 foot Ground Bond return lead. It allows ground bond test current to return to the ground bond tester. The test lead is terminated in an alligator clip.

Compatible Models:
3130, 3160, 5030DT, 7504SA, 7704, 8004, 8005, 8006



CBLHR-05M 5 Foot Ground Bond Magnetic Return Lead

This is a 5 foot Ground Bond return lead. It allows ground bond test current to return to the ground bond tester. The test lead is terminated in a magnetic clip that provides easy application to the DUT.

Compatible Models:
3130, 5030DT, 7504SA, 7704, 8004, 8005, 8006



CBLHR-15M 15 Foot Ground Bond Magnetic Return Lead

This is a 15 foot Ground Bond return lead. It allows ground bond test current to return to the ground bond tester. The test lead is terminated in a magnetic clip that provides easy application to the DUT.

Compatible Models:
3130, 5030DT, 7504SA, 7704, 8004, 8005, 8006



38490 40 Amp Ground Bond HC Return Lead

This is our standard 40 Amp Ground Bond return lead. It allows Ground Bond test current to return to the Ground Bond tester. The test lead is 5 foot in length and is terminated in an alligator clip.

Compatible Models:
3140, 8104, 8105, 8106



38624 10 Foot 40 Amp Ground Bond HC Return Lead

This is our 40 Amp Ground Bond return lead. It allows Ground Bond test current to return to the Ground Bond tester. The test lead is 10 feet in length and is terminated in an alligator clip.

Compatible Models:
3140, 8104, 8105, 8106



38625 15 Foot 40 Amp Ground Bond HC Return Lead

This is our 40 Amp Ground Bond return lead. It allows Ground Bond test current to return to the Ground Bond tester. The test lead is 15 feet in length and is terminated in an alligator clip.

Compatible Models:
3140, 8104, 8105, 8106



38626 25 Foot 40 Amp Ground Bond HC Return Lead

This is our 40 Amp Ground Bond return lead. It allows Ground Bond test current to return to the Ground Bond tester. The test lead is 25 feet in length and is terminated in an alligator clip.

Compatible Models:
3140, 8104, 8105, 8106



38719 5 Foot 40 Amp Ground Bond Magnetic Return Lead

This is our magnetized 40 Amp Ground Bond return lead. It allows Ground Bond test current to return to the Ground Bond tester. The test lead is 5 feet in length and is terminated in a magnetic clip that provides easy application to the DUT.

Compatible Models:
3140, 8104, 8105, 8106

This is our magnetized 40 Amp Ground Bond return lead. It allows Ground Bond test current to return to the Ground Bond tester. The test lead is 15 feet in length and is terminated in a magnetic clip that provides easy application to the DUT.

Compatible Models:
3140, 8104, 8105, 8106



CBLHC40-10TL 40 Amp Ground Bond Return Lead

This is a 40 Amp Ground Bond return lead. It allows Ground Bond test current to return to the Ground Bond Tester. The test lead is 10 foot in length and is terminated in a spade lug.

Compatible Models:
8105, 8106



38457 5 Foot 60 Amp Ground Bond Return

This is a five foot high current Ground Bond return lead. This lead comes standard with the 3160 and features a 4-wire connection to the tester. It is terminated in an alligator clip and allows ground bond tester current to return to the ground bond tester.

Compatible Models:
3160
